


Hard-wearing, slip-resistant matting perfect for commercial and industrial workplaces.



**Our number one defence against slippery environments, Vynagrip is heavy-duty matting that's designed to withstand all kinds of workplace liquids.**

Made from non-porous PVC with a diamond cut pattern, Vynagrip is impermeable to fluids and provides excellent drainage, making it ideal for environments where spillages are likely. It's also perfect for workplaces with standing employees: the two-layer construction provides comfortable cushioning and anti-fatigue properties proven to help boost productivity.



## Features:



Diamond cut pattern



Two layer open-grid construction



Made from non-porous PVC



Proven anti-fatigue properties



Comes in 10m (33') rolls or ramped modules



## Benefits:



Certified slip resistant (DIN 51130:R11, ASTM 1677: 1.0/0.9)



Excellent drainage (DIN 51130:V10)



Chemical, oil and acid resistant



Boosts productivity



Contours to uneven surfaces



## Plastic Extruders Ltd.

Russell Gardens, Wickford  
Essex, SS11 8DN  
+44 (0) 1268 571 116

UK + USA manufactured matting products:  
[plastexmatting.com](http://plastexmatting.com)



### Standard sizes:

	Vynagrip	Vynagrip and Vynagrip Plus	Vynagrip Modules
<b>Height</b>	15mm (5/8")	15mm (5/8")	15mm (5/8")
<b>Standard roll options</b>	5 x 0.6m (16'6" x 2')	10 x 0.6m (33' x 2')	
	5 x 0.91m (16'6" x 3')	10 x 0.91m (33' x 3')	
	5 x 1.22m (16'6" x 4')	10 x 1.22m (33' x 4')	
<b>Standard module options</b>			1.2 x 0.8m (4' x 2'5")
			1.5 x 1m (5' x 3'3")
<b>Weight</b>	7.6kg/m <sup>2</sup> (1.6lb/sq.ft)	7.6kg/m <sup>2</sup> (1.6lb/sq.ft)	7.6kg/m <sup>2</sup> (1.6lb/sq.ft)

Surface modules are supplied with factory fitted PVC ramped edging to four sides

### Tolerances:

	Height (+/- 0.5mm)	Length (0+0.3m)	Width (0+1cm)
<b>Vynagrip</b>	15 mm	5 m 10 m	60 cm 91 cm 122 cm
<b>Vynagrip Plus</b>	15 mm	10 m	60 cm 91 cm 122 cm

All dimensions are nominal

### Technical information:

<b>Acoustic</b>	Excellent sound absorption
<b>Anti-fatigue</b>	10% reduction in fatigue (University of Hertfordshire study, 1997).
<b>Chemical</b>	Resistant to most acids, alkalines and oils. You can read more about specific chemical resistances by downloading this <a href="#">information sheet</a> .
<b>Composition</b>	Flexible Polyvinyl Chloride (PVC)
<b>Electrical</b>	BS 2782: Part 2 Method 230A. Insulation resistance > 2000M Ω Electric strength = 12,600 volts
<b>Environment</b>	Vynagrip and Vynagrip Plus is 100% recyclable. When manufactured in black, Vynagrip and Vynagrip Plus is made using our post industrial recycled material. The recycled content averages at least 30%, but we strive for 100% wherever possible. We don't use any substances included in the SVHC list under REACH in any of our matting products..
<b>Fire</b>	EN ISO 13501-1:2007-Cfl-Sl.
<b>Hygiene</b>	Made from non-porous PVC that's naturally resistant to bacteria growth.
<b>Reversion</b>	Thermoplastic shrinkage can result in size reductions up to 2%. This may be accelerated in hot environments. You can read more about the causes of shrinkage by <a href="#">downloading this information sheet</a> .
<b>Rolling resistance</b>	ASTM F 2753: No apparent damage to the vinyl portion of the system after 1,000 cycles at 500lbs
<b>Slip resistance</b>	ASTM F 1677- Dry/Wet: 1.0/0.9 DIN 51130: R11, V10
<b>Thermal</b>	Designed to function at temperatures from -23°C and up to +60°C. Slight size variation may occur at temperature extremes.
<b>UV light</b>	Resistant to PVC degradation. The red colour isn't colourfast in direct sunlight.
<b>Warranty</b>	Four years. Visit our <a href="#">policies page</a> for more information about warranties


### Colours:



Black



Red



Blue



Black with yellow bands

More colours available upon request

### Installation:

Vynagrip's one-piece construction means installation is simple:

- Modules come with factory fitted edging around three sides and fit snugly against work stations
- Rolls are easy to cut on site
- Contours to uneven surfaces

### Cleaning:

Keeping Vynagrip looking good is easy:

- Easy to move; simply roll or lift to clean
- No special cleaning tools needed
- Easy to wash down with a high pressure hose

### Ancillaries:

#### > Vynagrip and Vynagrip Plus

PVC edging (H: 14mm, W: 60mm)



Supplied in rolls of 10.1m (33') length with cold welding paste. Comes in black, dark grey, dark brown, holly green, Oxford blue, yellow. Size: 14mm x 60mm x 10.1m (9/16" x 2 1/2" x 33')

PVC edging (H: 14mm, W: 100mm)



Supplied in rolls of 10.1m (33') length with cold welding paste. Comes in black, dark grey and yellow. Size: 14mm x 100mm x 10.1m (9/16" x 3 3/4" x 33')

Aluminium edging (H: 15mm)



Supplied in sections of 2m (6'6") length with fixing screws and plugs. Comes in anodised aluminium and powder coated yellow. Size: 15mm x 45mm x 2m (5/8" x 1 13/16" x 6'6")

PVC snap track (H: 14mm)



Two-part snap track that can be welded together to join rolls end-to-end or side-to-side to cover large areas. Supplied with cold welding paste. Comes in black and dark grey. Size: 14mm x 2.5m (9/16" x 8'2")

Large floor hooks (H: 14mm)



For securing sections of matting to the floor. Supplied in packs of 10 with screws and plugs

Small floor hook (H: 14mm)




For securing sections of matting to the floor. Supplied in packs of 20 with screws and plugs

### Ancillaries:


#### > Vynagrip and Vynagrip Plus

Connector clips: side-to-end (H: 14mm)



For joining sections of matting together side-to-side. Supplied in packs of 10

Connector clips: dual purpose (H: 14mm)



For joining sections of matting together side-to-side or end-to-end. Supplied in packs of 10